




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G06F 17/00</b>	<b>A1</b>	(11) International Publication Number: <b>WO 97/25678</b> (43) International Publication Date: 17 July 1997 (17.07.97)
<p>(21) International Application Number: PCT/US97/00748</p> <p>(22) International Filing Date: 13 January 1997 (13.01.97)</p> <p>(30) Priority Data: 08/585,183 11 January 1996 (11.01.96) US</p> <p>(71) Applicant: COMPUCYTE CORPORATION [US/US]; 12 Emily Street, Cambridge, MA 02139-4517 (US).</p> <p>(72) Inventors: KAMENTSKY, Louis, A.; 180 Beacon Street, Boston, MA 02116 (US). WEISSMAN, Mark; 270 Pelham Island Road, Wayland, MA 01778 (US). KAMENTSKY, Lee, D.; 32 Dodge Street, Arlington, MA 02174 (US). GERSHMAN, Russell; 93 Plymouth Street, Middleboro, MA 02346 (US). POMEROY, B., Martin; 33 Griffin Road, Framingham, MA 01701 (US).</p> <p>(74) Agent: NISSENBAUM, Israel; Graham &amp; James L.L.P., 24th floor, 885 Third Avenue, New York, NY 10022 (US).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> With international search report.</p>	

(54) Title: NETWORK REVIEW AND ANALYSIS OF COMPUTER ENCODED SLIDES

## (57) Abstract

A network system for review and analysis of microscope slides and specimens which were originally computer encoded from a microscope (1), and viewing locations and events of interest on the slide, with such information being stored on a network file server (3). The data also includes information regarding the manner in which the initial examination was conducted, for quality control purposes. The computer encoded information is retrievable at all remote locations of the network (either local or connected via modem) for supervisor review or for pathologist analysis (1). The network is further constituted by microscope (8) sites having similar computer encoding devices attached thereto, which function, in this aspect, as computer terminals of the network. For enhanced analysis, the computer terminals have direct access to patient background information, e.g., such as from an HIS (hospital information system) (7) for simultaneous slide analysis review in relation to the medical history of the patient.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LJ	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

**NETWORK REVIEW AND ANALYSIS OF COMPUTER ENCODED SLIDES****FIELD OF THE INVENTION**

This invention relates to computerized review of computer encoded microscope slides after examination of specimens  
5 thereon, and particularly with respect to multi-site examination thereof.

**BACKGROUND OF THE INVENTION**

Various devices exist for use in the review of previously  
10 examined microscope slides for facilitated re-examination, as a quality control, and as a gauge with respect to the degree of reliability of initial slide examination test results.

One of such devices and methods of re-examination is disclosed in the parent of the present application wherein an encoder device is described which retrievably provides computer encoding  
15 of positions of the slide which were examined initially. Movement of the microscope stage on which the slide is positioned correspondingly records position location on a computer generatable image of a slide. As a result, retrieval of the computer encoded examination provides a slide image  
20 having markings thereon which indicates areas of the slide which were examined (and the absence of which indicates areas which were not examined). Co-pending application, serial no. 08/491,414, filed June 16, 1995, provides a further enhancement for determining which areas were examined, for how long, whether  
25 there was overlapping of viewing, the percentage of the slide area screened and the like. In such co-pending application, a grayscale display is used to indicate relative dwell time at each location (or pixel of the computer representative image), whereby during rapid screening, the central area of a moving  
30 circular cursor that sweeps out a track on the screen, is darker than the edges of the field of view. In addition, as a screener overlaps the column or row on the next pass, the time spent on the overlapping edges is added, and the edges darken to indicate additional inspection time. Based on variations in the  
35 grayscale, the device further provided the percentage of

overlapping fields as a useful measure of screening performance, which screeners and screening reviewers were able to use to refine performance, i.e., too little overlap can lead to false negative findings, while too much overlap indicates inefficient performance. A supervisor is thereby provided with a rational and efficient quality control method for choosing which specimens to review for teaching and quality control purposes.

Use of the internal computer clock further enabled placement of the markings in a time dependent manner such that a determination could be made with respect to the examination dwell time in the examined areas.

As a further feature, in the parent application, selected marked areas of specified locations in the slide specimens were able to be marked in computer memory (visually or with audio) to indicate whether such areas on the actual slide are of particular interest and if so, with pre-determined coding, to additionally mark such slide viewing areas. As a result, the areas having such additional interest markings are thereby able to be re-examined with greater ease in location and re-location.

Other systems extant, operate with actual imaging of slide contents, such as with video cameras and the like, coupled with slide location mapping for retrieval location of specific areas of interest. Video images are digitized for facility in computer storage and retrieval purposes. However, all of the slide re-examination systems and procedures have been confined to a single site, and review of the original slide or image thereof, and, in some systems, with a computerized review of the encoded procedures utilized in obtaining the initial results.

#### SUMMARY OF THE INVENTION

It is accordingly an object of the present invention to provide a means for multiple simultaneous review of encoded information obtained from the slide analysis procedures of a microscope slide, including the manner in which the slide analysis was conducted and optionally including stored images of the slide.

It is a further object of the present invention to provide such means for review at two or more networked remotely located microscope sites linked to computer encoder-terminals.

5 It is yet another object of the present invention to permit the multiple review of flagged slide specimen view sites at two or more remotely located terminal sites.

10 It is still yet another object of the present invention to provide network capability at the terminal sites, for correlating slide information together with patient history and/or together with comparative observation information to resolve possible ambiguities in interpretation.

15 It is another further object of the present invention to provide automatic location and review of the flagged slide specimen view sites.

It is a still further object of the present invention to provide report generation in HIS (health information systems) systems for full patient records.

20 These and other objects, features and advantages of the present invention will become evident from the following discussion and drawings in which:

#### BRIEF DESCRIPTION OF THE DRAWINGS

25 Figure 1 schematically depicts a networked system of microscope sites, with linked computer encoders; HIS network file server; data supply system; and cytometer station;

Figure 2 is a window field showing slide review, patient history and information and selected recorded images of the slide;

Figure 3 is a report window field; and

30 Figure 4 is a comparative window between patient slide and library-recalled slide image.

## DETAILED DESCRIPTION OF THE INVENTION

Generally the present invention comprises method for network reviewing of a specimen slide and the manner in which a prior microscope examination of the specimen slide was conducted and the networked system. The method relates to selected details of the specimen of the specimen slide and the manner of examination thereof which were computer encoded, during prior scanning examination thereof. The original examination having been conducted with a microscope having viewing means and a moving slide stage, on which the specimen slide was mounted, wherein encoding of the details of the specimen and the manner of examination thereof was effected by:

a) operatively linking computer means, with correlation movement sensor means, to the movable slide stage of the microscope, to correlatively record movement of the slide stage in an x-y direction plane in which the slide stage is movable;

b) recording movement and various locations of the slide stage during the microscope examination of the specimen slide, at various locations on the specimen slide, by means of the linked computer means, pursuant to programmed instructions, into computer storage means; and wherein the computer means, pursuant to additional programmed instructions automatically records, into the computer storage means, information relating to the stored various locations and the manner in which the examination was conducted. The network reviewing method comprises the step of causing the computer storage means to be independently accessible by at least two separate microscope stations in a network, each of the stations comprising a microscope and computer means, with each of the microscope stations being separately individually linked to at least one computer means capable of recalling the stored movements and location information from the storage means for review at a location remote from the microscope used in the original examination.

In a preferred embodiment the present invention comprises a method for network reviewing of a specimen slide and the manner

in which a prior microscope examination of the specimen slide was conducted, wherein selected details of the specimen of the specimen slide and the manner of examination thereof were computer encoded, during prior scanning examination thereof with  
5 a microscope having viewing means and a moving slide stage, on which the specimen slide was mounted, wherein encoding of the details of the specimen and the manner of examination thereof was effected by:

10 a) operatively linking computer means, with correlation movement sensor means, to the movable slide stage of the microscope, to correlatively record movement of the slide stage in an x-y direction plane in which the slide stage is movable;

15 b) recording movement and various locations of the slide stage during the microscope examination of the specimen slide, at various locations on the specimen slide, by means of the linked computer means, pursuant to programmed instructions, into computer storage means; and wherein the computer means, pursuant to additional programmed instructions automatically records, into the computer storage means, at the stored various  
20 locations, pre-determined indicia, with said indicia correlating to the microscope viewing area location on the specimen, and wherein said indicia, correlating to viewing area locations of interest were marked and recorded with a distinguishing marking for subsequent review recognition; said network reviewing method  
25 comprising the steps of:

a) causing the computer storage means to be independently accessible by at least two separate microscope stations in a network, each of said stations comprising a microscope and computer viewing means, with each of said microscope stations  
30 being separately individually linked to at least one computer means capable of recalling said stored movements, locations and indicia from the storage means for review on the computer viewing means:

35 b) recalling, at one or more of said microscope stations, from said computer storage means, a computer generated image of a slide with said indicia thereon, onto the viewing means of the respective microscope station, for review of the manner in which a prior microscope examination of the specimen slide was conducted; and

i) placing the specimen slide on the movable slide stage of the microscope, at the respective microscope station, with the microscope thereat being further operatively linked with the computer means, by correlation movement sensor means;

5 ii) moving the stage, with concomitant specimen slide movement, with correlation of each subsequent microscope viewing area with indicia on the computer generated image, by indicator means, whereby correlated indicia having a distinguishing marking thereon is directly viewable with the microscope.

10 With reference to the parent application, the present invention also comprises a method for network reviewing of a specimen slide and the manner in which a prior microscope examination of the specimen slide was conducted, wherein selected details of the specimen of the specimen slide and the manner of examination  
15 thereof were computer encoded, during prior scanning examination thereof with a microscope having viewing means and a moving slide stage, on which the specimen slide was mounted, wherein encoding of the details of the specimen and the manner of examination thereof was effected by:

20 a) operatively linking computer means, with correlation movement sensor means, to the movable slide stage of the microscope, to correlatively record movement of the slide stage in an x-y direction plane in which the slide stage is movable;

b) recording movement and various locations of the slide  
25 stage during the microscope examination of the specimen slide, at various locations on the specimen slide, by means of the linked computer means, pursuant to programmed instructions, into computer storage means; and wherein the computer means, pursuant to additional programmed instructions and an internal clock of  
30 the computer means, automatically recorded, into the computer storage means, at the stored various locations, pre-determined indicia at predetermined time intervals, determined by said internal clock, with said indicia correlating to the microscope viewing area location on the specimen, at the predetermined time  
35 intervals; and wherein said indicia, correlating to viewing area locations of interest were optionally marked and recorded with a distinguishing marking for subsequent review recognition; said network reviewing method comprising the steps of:



a) causing the computer storage means to be independently accessible by at least two separate microscope stations in a network, each of said stations comprising a microscope and computer viewing means, with each of said microscope stations being separately individually linked to at least one computer means capable of recalling said stored movements, locations and indicia from the storage means for review on the computer viewing means:

b) recalling, at one or more of said microscope stations, from said computer storage means, a computer generated image of a slide with said indicia thereon, onto the viewing means of the respective microscope station, for review of the manner in which a prior microscope examination of the specimen slide was conducted; and

if indicia correlating to sites of interest have been marked with a distinguishing marking:

i) placing the specimen slide on the movable slide stage of the microscope, at the respective microscope station, with the microscope thereat being further operatively linked with the computer means, by correlation movement sensor means;

ii) moving the stage, with concomitant specimen slide movement, with correlation of each subsequent microscope viewing area with indicia on the computer generated image, by indicator means, whereby correlated indicia having a distinguishing marking thereon is directly viewable with the microscope.

The present invention includes a network system for review and analysis of computer encoded microscope slides and specimens which were originally computer encoded from a microscope (attached via an encoder device to a local computer site), during an initial examination with an encoding system. The encoding includes parameters of viewing locations and events of interest on the slide, with such information being stored on a networked file server. The encoding also includes information regarding the manner in which the initial examination was conducted, for quality control purposes. The computer encoded information is retrievable at all remote locations of the network (either local or connected via modem) for supervisor review or for pathologist analysis. The network is further

constituted by microscope sites having similar computer encoding devices attached thereto, which function, in this aspect, as computer terminals of the network. For enhanced analysis, the computer terminals have direct access to patient background information, e.g., such as from an HIS (hospital information system) for simultaneous slide analysis review in relation to the medical history of the patient. For diagnostic support, the computer terminals are networked with an on-line library of cell type images for comparison with the slide being examined. Slide diagnosis is either directly with the original slide on the microscope or with a scanned digital image of the slide stored in the network server or CD-ROM and retrieved on the computer terminal. The microscope is optionally motor driven, with computer control, to relocate slide images only at designated sites.

The following discussion relates to the various required and optional examination steps involved in the present invention:

1) Specimen Selection:

Providing means to communicate encoding system data is not useful unless means are provided for selecting microscopic slides that require review by another individual. Means are accordingly provided for selecting appropriate computer files generated by each of multiple encoding systems to create new files for supervisor' or pathologist' encoding systems who review prior slide examinations. A user interface to perform this task is therefore an integral part of the encoding system.

2) Demographics:

Diagnostic judgments are based not only on the appearance of specific cells viewed microscopically, but on patient demographics and prior clinical history. Diagnostic decisions can be aided if the encoding system provides medical information from a Hospital Information System (HIS) to support these decisions. This affords an important additional benefit to the Hospital Information System in that not only is patient information available for use by the encoding system user, but that the encoding system itself can provide a computer terminal

for entry of patient data, derived from observations of the slide, directly into the Hospital Information System for immediate use by others. Such data can be numeric data from a differential cell count of a blood smear, urine specimen,  
5 microbiology specimen or body fluid cytospin or it can be a cytologic or anatomic pathologic diagnosis text report.

**3) Diagnostic Decision Support:**

Diagnostic decisions, after observation of potentially pathologic cells on a specimen slide, are sometimes ambiguous  
10 even utilizing prior patient information. The pathologist will often review images of cells by looking at other microscope slides, images in textbooks and images on 35mm film slides in order to compare them with the cells of the patient specimen to reach a diagnosis. In accordance with the present invention the  
15 encoding system, is capable of supporting diagnostic decisions by retrieving images from files and displaying them with the specimen cell images digitized by means of a video camera. In addition, patient demographics and prior data entries are retrievable in the network, to suggest what should be observed  
20 on the microscope slide and what diagnoses may be possible.

**4) Report Generation:**

Anatomic pathology or cytology diagnoses must be reported and a permanent record must be generated in the Hospital Information System. This report should include encoding system data such as  
25 maps of the location and types of unusual cells as well as images of some of these cells digitized by means of a video camera. The encoding system data permits better document the efficacy of the laboratory as well as providing images and cell locations for use during comparisons with cells from subsequent  
30 examinations, whereby it is possible to follow and document disease progression.

**5) Scanning Instruments:**

Instruments for scanning specimens of cells on microscope slides, using a laser or a video camera, identify specific cells  
35 by their constituents, their genotype or phenotype, or their pathology. This type of instrument is used in medical and

research laboratories, with some of these instruments being capable of recording the position on the microscope slide of each cell measured. These devices are interfaced, in accordance with a preferred embodiment of the present invention, to an encoding system in order:

1) to annotate cells or areas of a slide containing a specific type of cell (such as a cancer area) so that only these cells or the specific area will be scanned by the instrument; or

2) after slides are scanned by the instrument, the encoding system can be used to locate and visually review, report on and include images of specific cells based on properties found by the instrument.

**6) Automatic Relocation:**

In order to minimize time and effort of pathologists, in a preferred embodiment, the encoding system is comprised of a motorized stage. As a result, cell relocation of annotated slide areas is mechanized.

**DETAILED DESCRIPTION OF THE DRAWINGS AND  
THE PREFERRED EMBODIMENTS**

With reference to the drawings, Fig. 1 is a diagram of the preferred embodiment of the networked encoder system. One or more encoders 1, each consisting of a microscope equipped with stage position encoders, are interfaced with a microprocessor, a display screen and a keyboard. These encoders are used by laboratory personnel to screen and review microscope slides as described in the parent of this application. In accordance with the present invention each encoder contains an additional circuit, such as a MAX491 transmitter and receiver chip connected directly to the microprocessor's UART input/output lines, which enables communication via asynchronous line protocol using RS485 line drivers. The receiver and transmitter chip are connected to a twisted pair of wires 2 running throughout a laboratory area having multiple encoders, with each encoder being connected to the wires, i.e., "Daisy Chained". The wires are connected to PC CPU 3, which serves as the encoder system LAN server. One or more encoder DS Systems 4 and

scanning instruments 5 may be connected to the network, provided that each uses a computer containing a network interface card, e.g., FASTCOM serial adapter board (Industrial Computer Source).

5 Communication between the server and all encoders and other devices connected on the network wires 2 is effected by means of appropriate software with communication being in forms of packets having a defined structure. This structure contains the address of a device, a command or status byte, error control information and optionally a data field. Each communication on  
10 the network consists of the server sending a single packet to a particular device, the first byte of which is one device's address. The devices determine if the address corresponds to their address and only the one device with the correct address will receive the remainder of the packet. It will check for  
15 errors and respond with a single packet sent to the server. The server continually polls all devices to determine if any need to either send data to the server or to receive data from it.

The server 3 of Figure 1 is a standard PC computer operating the encoder System network using the Microsoft Windows™ (3.1 or 95),  
20 NT or other similar operating system. Any commercially available Ethernet card can be inserted into a spare buss circuit board slot in the computer. The Ethernet card is in turn connected by wire 6 to any other computer with an operating system compatible with the Microsoft Windows operating system on  
25 the server. The encoder software utilizes an ODBC standard database structure to store and retrieve specimen data and patient demographics. Medical organizations are adopting standards such as HL7 to provide standard names of specific fields to be used in data files. By combining these standards  
30 it is possible for computer database programs of different systems to communicate with each other to either find or send specific items of data.

With a Hospital Information System link, encoder users are able to retrieve specimen lists entered at an accession desk and use  
35 these to select the current specimen being examined as well as being able to call up and display patient demographics and

history to help reach decisions. Optionally results may be directly read into the Hospital Information System, with the encoders can serving as data terminals for microscope users to enter data in the Hospital Information System.

5 As shown in Figure 1, the encoder DS sub System comprises a PC computer 4 configured with a CD-ROM drive, encoder software, Diagnosis Decision Support software (DDSS), and interface cards connecting the PC to a microscope equipped with encoder stage position encoders and a CCD video camera 8.

10 The DDSS component comprises 1) a database of microphotographic examples of proven cases at scanning and high-power magnifications, 2) algorithms to help direct the microscopic examination of the specimen, 3) expert commentary on differential diagnoses with recommendations for further  
15 diagnostic pathology testing (immunohistochemistry, special stains, etc.), 4) regularly updated medical references, and 5) software utilities enabling pathologists to capture, archive, and retrieve their own images/cases. These components are preferably on CD-ROM disks.

20 The encoder DS System provides practice guidelines for pathologists in the diagnosis of difficult cases; and facilitates diagnostic consistency in rapidly evolving areas of cytopathology specimen procurement such as fine needle aspiration. Quality assurance efforts are thereby enhanced by  
25 providing more standardized criteria and algorithms for specimen diagnosis; and it provides up-to-date knowledge about the criteria used by experts to support specific diagnoses to thereby avoid common pitfalls.

In practice, the pathologist places the specimen on a network  
30 linked microscope with encoder and uses the PC to access demographic information from the Hospital Information System. The DDSS program then generates algorithms to help direct the microscopic examination of the specimen. The precise location of significant features of the specimen identified by a  
35 pathologist is determined by the encoder with programmed

instruction and saved for future relocation. Additionally,  
images of the specimen captured by the CCD camera, are compared  
alongside images of proven cases in the DDSS database. These  
specimen images may also be incorporated into a pathologist's  
5 report and saved into his or her own database and used for  
future reference. DDSS algorithms identify a "most likely"  
diagnosis based on the pathologist's input into the diagnostic  
algorithm, the program then is able to make recommendations for  
further diagnostic pathology testing and to provide up-to-date  
10 medical references.

As shown in Fig. 1 a PC computer 4 is interfaced with a  
microscope stage encoder. Encoder interface boards are  
commercially available (e.g., Technology80, Inc.). With  
appropriate software a PC computer, operating under Microsoft  
15 Windows is able to perform encoder functions using encoder  
generated data or data from the encoder system network 2. The  
PC computer based encoder (encoder DS) 4 is connected to a  
microscope equipped with a CCD video camera 8 arranged so that a  
microscopic field can be viewed or imaged into the camera. The  
20 video camera in turn is connected to a commercially available  
frame grabber board in the PC computer (e.g., from Hauppauge  
Computer Works, Inc.). Appropriate software provides for the  
additional functions of generating a report, form 9 of Fig. 2,  
which can be electronically stored or printed. This form  
25 contains encoder data including the annotation map 10. A  
reviewer is then able to find cells on a slide by moving the  
microscope stage until a visible cursor 11 on the annotation map  
is coincident with an annotation mark such as 12. Annotations  
for various types are differentiated by different colors, not  
30 visible in the black and white rendering of Fig. 2. When the  
cursor is within a preset distance from an annotation, the image  
of the microscope field is made to appear in a window 12 on the  
computer monitor and the annotation number in the area 13. To  
do this, software was written to utilize the frame capture  
35 capability of the frame grabber board and the manufacturer's  
display software. Superimposed on the image is a button 14  
which can be pushed using the computer's mouse to store the  
image in computer memory. The user is able to indicate the

microscope objective used by clicking one of the buttons on the panel 15 with the mouse. The user can also store multiple images of any field at different focuses of the microscope at any of the magnifications. All such images are stored and appropriately indexed with appropriate software instruction. In a preferred embodiment the microscope is equipped with a mechanism to automatically move the focus position as images are being captured and stored. Review and image capture is then repeated for each annotation by clicking the Next Field button 16 or a different slide can be reviewed by clicking the Next Slide button. It is possible to generate computer records not only with encoder data, but records containing images of the cells causing the annotations. It is also possible to include database fields consisting of voice records for vocally commenting on cells or the specimen. This can be implemented with the addition of a commercially available PC computer sound card and software to place recorded files into the database.

A further Reporting Window 18 is shown in Fig. 3. The patient's accession number is selected through icon 19 or entered in box 20, at which time the list of annotations found on the slide appear in box 21. Upon selecting an annotation number, all of the images of that slide field are transferred from disk storage to RAM storage for instantaneous viewing. The user can then, with a mouse, select a magnification using the buttons in the field 22 and a focus using the set of two up and down focus buttons 23 to call up and display in the Window 24 the appropriate image of the annotated microscope field. Window 18 also provides Text Boxes 25 for typing in the cytology diagnosis and 26 for later typing in the results of any histology done on the patient. Concurrence of these two text reports may be given a numerical value, with this value being stored along with the text and images for each slide for use in laboratory quality control.

There are least four types of instruments, hematology analyzers, PAP smear analyzers, image analyzers and the CompuCyte LSC™ (trademark) laser scanning cytometer, in which microscope slides are scanned, the data from scans is processed, cells are



digitally located and isolated and the cells are characterized, based on the scan data. One or more of the instruments can be interfaced with at least one of the microscope stations on network in accordance with the present invention.

5 With each instrument, the cells can be classified and their type and location on the slide recorded in a digital medium. The LSC (5 of Fig. 1) is an example of a scanning instrument which can be connected to the encoder system network 2 by inserting a FASTCOM network card in the LSC's PC computer. The LSC can scan  
10 slides stained with fluorescent dyes to measure the constituents and morphology of cells on the slide and generate a computer database file containing a set of constituent values, morphology values and slide position values for every cell found by it on the slide. The position coordinates of the LSC can be  
15 calibrated to the same positional frame as the encoder system devices using a calibration slide, as described in the copending application.

Slides to be examined with the LSC are often made by touching a surgically resected tissue to a slide or they may use tissue  
20 sections fixed to the slide. They therefore may contain normal as well as pathologic areas corresponding to normal and abnormal areas of the original tissue. It is advantageous to indicate to the LSC, by visual observation, the type of cells in each area of the slide, or to mark specific cells prior to scanning the  
25 slide. For example, a specimen may contain many more normal cells than cancer cells and if all cells were scanned, the resulting statistics may hide the characteristics of the cancer cells. If only the cancer area were scanned, the resulting data is more useful in determining treatment of the cancer.  
30 Accordingly, the slide is placed on an encoder DS, connected to a phase or fluorescent microscope. Cells on the slide are viewed and the stage is moved to specific areas of interest. Corners of the slide area to be scanned are annotated or specific locations on the slide to be scanned by the LSC are  
35 annotated in a fixed area centered on the annotation position. The positional frame of reference is translated back to that of the LSC. The LSC itself already provides the slide area and

specific cell marking function by allowing annotation of corner positions or specific cells by the user, while the slide is on the stage of the LSC. Annotations may be made on an encoder as well as on the LSC.

5 In an embodiment wherein the X and Y axis movement of the microscope stage is motorized, the encoder can automatically relocate events of interest during the slide review process which had been electronically marked during the screening process. Efficient review is therefor possible in order to ease  
10 the heavy burden placed on cytopathologists. In particular, events to be reviewed can be keyed by the type of event, i.e., all positive events reviewed first followed by all atypicals, etc.

In addition to motorization, for familiarity of users with  
15 normal operation, the microscope stage may be also manually controllable through the standard stage motion mechanisms used in normal microscope operation, such as by means of a dual concentric shaft encoder. The dual encoder is mounted on the microscope and equipped with dual knob similar to those of a  
20 standard microscope. Motion of the outer knob and encoder generates pulses and the direction sense so that the motorized stage is made to move in the Y direction. Motion of the inner knob and encoder causes corresponding X motion of the microscope stage. Other devices such as a mouse or pointing tablet  
25 (Glidepoint®, Alps Electric, San Jose, CA) may be used to cause slide movement.

It is understood that the details of the above system and the various preferred embodiments are not to be construed as  
30 limitations of the present invention and that features and changes in the system may be made without departing from the scope of the present invention as set forth in the following claims.

1. A method for network reviewing of a specimen slide and the manner in which a prior microscope examination of the specimen slide was conducted, wherein selected details of the specimen of the specimen slide and the manner of examination thereof were computer encoded, during prior scanning examination thereof with a microscope having viewing means and a moving slide stage, on which the specimen slide was mounted, wherein encoding of the details of the specimen and the manner of examination thereof was effected by:

a) operatively linking computer means, with correlation movement sensor means, to the movable slide stage of the microscope, to correlatively record movement of the slide stage in an x-y direction plane in which the slide stage is movable;

b) recording movement and various locations of the slide stage during the microscope examination of the specimen slide, at various locations on the specimen slide, by means of the linked computer means, pursuant to programmed instructions, into computer storage means; and wherein the computer means, pursuant to additional programmed instructions and an internal clock of the computer means, automatically recorded, into the computer storage means, at the stored various locations, pre-determined indicia at predetermined time intervals, determined by said internal clock, with said indicia correlating to the microscope viewing area location on the specimen, at the predetermined time intervals; and wherein said indicia, correlating to viewing area locations of interest were optionally marked and recorded with a distinguishing marking for subsequent review recognition; said network reviewing method comprising the steps of:

a) causing the computer storage means to be independently accessible by at least two separate microscope stations in a network, each of said stations comprising a microscope and computer viewing means, with each of said microscope stations being separately individually linked to at least one computer means capable of recalling said stored movements, locations and indicia from the storage means for review on the computer viewing means:

b) recalling, at one or more of said microscope stations, from said computer storage means, a computer generated image of a slide with said indicia thereon, onto the viewing means of the

respective microscope station, for review of the manner in which a prior microscope examination of the specimen slide was conducted; and

if indicia correlating to sites of interest have been marked with a distinguishing marking:

i) placing the specimen slide on the movable slide stage of the microscope, at the respective microscope station, with the microscope thereat being further operatively linked with the computer means, by correlation movement sensor means;

ii) moving the stage, with concomitant specimen slide movement, with correlation of each subsequent microscope viewing area with indicia on the computer generated image, by indicator means, whereby correlated indicia having a distinguishing marking thereon is directly viewable with the microscope.

2. A method for network reviewing of a specimen slide and the manner in which a prior microscope examination of the specimen slide was conducted, wherein selected details of the specimen of the specimen slide and the manner of examination thereof were computer encoded, during prior scanning examination thereof with a microscope having viewing means and a moving slide stage, on which the specimen slide was mounted, wherein encoding of the details of the specimen and the manner of examination thereof was effected by:

a) operatively linking computer means, with correlation movement sensor means, to the movable slide stage of the microscope, to correlatively record movement of the slide stage in an x-y direction plane in which the slide stage is movable;

b) recording movement and various locations of the slide stage during the microscope examination of the specimen slide, at various locations on the specimen slide, by means of the linked computer means, pursuant to programmed instructions, into computer storage means; and wherein the computer means, pursuant to additional programmed instructions automatically records, into the computer storage means, at the stored various locations, pre-determined indicia, with said indicia correlating to the microscope viewing area location on the specimen, and wherein said indicia, correlating to viewing area locations of interest were marked and recorded with a distinguishing marking for subsequent review recognition; said network reviewing method

comprising the steps of:

- 5 a) causing the computer storage means to be independently accessible by at least two separate microscope stations in a network, each of said stations comprising a microscope and computer viewing means, with each of said microscope stations being separately individually linked to at least one computer means capable of recalling said stored movements, locations and indicia from the storage means for review on the computer viewing means:
- 10 b) recalling, at one or more of said microscope stations, from said computer storage means, a computer generated image of a slide with said indicia thereon, onto the viewing means of the respective microscope station, for review of the manner in which a prior microscope examination of the specimen slide was
- 15 conducted; and
- i) placing the specimen slide on the movable slide stage of the microscope, at the respective microscope station, with the microscope thereat being further operatively linked with the computer means, by correlation movement sensor means;
- 20 ii) moving the stage, with concomitant specimen slide movement, with correlation of each subsequent microscope viewing area with indicia on the computer generated image, by indicator means, whereby correlated indicia having a distinguishing marking thereon is directly viewable with the microscope.
- 25 3. A method for network reviewing of a specimen slide and the manner in which a prior microscope examination of the specimen slide was conducted, wherein selected details of the specimen of the specimen slide and the manner of examination thereof were computer encoded, during prior scanning examination
- 30 thereof with a microscope having viewing means and a moving slide stage, on which the specimen slide was mounted, wherein encoding of the details of the specimen and the manner of examination thereof was effected by:
  - a) operatively linking computer means, with correlation
  - 35 movement sensor means, to the movable slide stage of the microscope, to correlatively record movement of the slide stage in an x-y direction plane in which the slide stage is movable;
  - b) recording movement and various locations of the slide stage during the microscope examination of the specimen slide,

at various locations on the specimen slide, by means of the linked computer means, pursuant to programmed instructions, into computer storage means; and wherein the computer means, pursuant to additional programmed instructions automatically records,  
5 into the computer storage means, information relating to the stored various locations; said network reviewing method comprising the step of:

causing the computer storage means to be independently accessible by at least two separate microscope stations in a  
10 network, each of said stations comprising a microscope and computer means, with each of said microscope stations being separately individually linked to at least one computer means capable of recalling said stored movements and location information from the storage means for review at a location  
15 remote from the microscope used in the original examination.

4. The method of claim 3, wherein the location information comprises a grayscale display, which indicates by shades of increasingly darker shades of gray increasing dwell time during the original examination, degree of overlap of viewing areas and  
20 proximity to the center of a viewing area, whereby the degree of efficacy of the original examination may be determined a remote location.

5. The method of claim 3, wherein the separate microscope stations are further independently linked to a hospital HIS  
25 system whereby the computer viewing means are made to provide simultaneous slide analysis review in relation to the medical history of a patient from whom the specimen was derived.

6. The method of claim 3, wherein areas on the slide specimen, selected for additional review during said  
30 examination, are video digitized areas representative in appearance of the areas on the slide specimen.

7. The method of claim 6, wherein the separate microscope stations are further independently linked to a library data base of known slide specimen images whereby the video digitized areas  
35 are visually compared to known slide specimens in a side by side comparison.

8. The method of claim 3, wherein at least one of the separate microscope stations is further independently linked to one or more cell analysis instruments, whereby cell analysis of

other specimens from the same source as the specimen of the prior microscope examination, is effected by the cell analysis instruments and wherein the analysis data from the cell analysis instruments and the results of the prior microscope examination are simultaneously available at the at least one of the separate microscope stations, for review thereof.

9. The method of claim 8, wherein cell analysis instruments are at least one of a hematology analyzer, PAP smear analyzer, image analyzer and laser scanning cytometer.

10. The method of claim 9, wherein the instrument is a laser scanning cytometer.

11. The method of claim 3, wherein at least one of the separate microscope stations each have microscopes with motor driven stages, with computer control, to re-scan slides or slide images only at viewing area locations of interest which were marked and recorded with a distinguishing marking.

12. The method of claim 8, wherein at least one of the separate microscope stations provide at least one of anatomic pathology and cytology diagnosis reports to a central Hospital Information System, where a permanent record thereof is generated.

13. The method of claim 3, wherein during said prior examination, multiple images of selected fields, at different focuses of the microscope and at any of the magnifications are stored and indexed, and wherein microscopes at the microscope stations are equipped with means to automatically move a focus position as images are being captured, stored, and recalled.

14. A network of interconnected microscope stations, with each station comprising a microscope operatively linked to computer means wherein information relating to a slide specimen being examined by the microscope is stored by the computer means and is thereby made accessible to other microscopes and computer means at each of the interconnected microscope stations.

15. The network of claim 14, wherein each of the interconnected microscope stations comprises a terminal for at least one data base having information relevant to appropriate examination of the slide specimen.

16. The network of claim 15, wherein the data base comprises a Hospital Information System and wherein the slide

specimen is from a patient whose medical records are contained in the Hospital Information System.

17. The network of claim 16, wherein selected areas of the slide specimen are converted to video digitized images by conversion and storage means, with said images being accessible at the interconnected microscope stations and wherein the data base further includes a library data base of known slide specimen images whereby the video digitized areas are visually compared to known slide specimens in a side by side comparison on video display means at any of the interconnected microscope stations.


18. The network of claim 14, wherein the network further includes at least one cell analysis instrument and wherein at least one of the interconnected microscope stations comprises a terminal for receipt of analysis from the cell analysis instrument.

19. The network of claim 16, wherein each of the interconnected microscope stations further comprises means for the generation of a report into the Health Information System for the patient, based on the slide specimen examination.



1 / 4

Figure 1 Pathfinder System Network



2 / 4

Fig 2

Cytology Report Form

**CompuCyt Medical Center**  
238 Main Street Cambridge, MA 02142

**CYTOLOGY REPORT** Sep 11, 1995

Patient Name  Accession Number  Slide Num.

Type  Specimen Comments  Primary Diagnosis

Screening ID  Time Min.  Coverage %  Overlap %

Annotation Map Has Critical Area

10 —

11

12

13

File Options Adjust Image

16

17

12'

14

3 / 4

Fig 3

CompuCyt Medical Center  
238 Main Street Cambridge, MA 02142

**CYTOLOGY REPORT**

Patient Name: JAMES Accession Number: 11833

Annotation Selection: 1  
2

Focus: 23

**CYTOPATHOLOGY DIAGNOSIS:**

**HISTOLOGY DIAGNOSIS:**


24

25

26

4 / 4

Figure 4



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US97/00748**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(6) : G06F 17/00

US CL : 364/551.01

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 364/551.01, 525,550, 468.15, 468.18

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 4,888,714 (DINGLE) 19 December 1989, col. 1 and col. 3.	14-19
Y	US, A, 5,353,399 (KUWAMOTO et al.) 04 October 1994, cols. 9-10.	14-19
P,Y	US, A, 5,581,487 (KELLY et al.) 03 December 1996, cols. 6-9.	1-19

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be part of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

30 MARCH 1997

Date of mailing of the international search report

16 APR 1997]

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Authorized officer

ELLIS B. RAMIREZ

Facsimile No. (703) 305-3230

Telephone No. (703) 305-3800

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**